


#### USER MANUAL

# **Heavy Duty** DIGITAL LEVEL

**DWL 600 F** (0.05° Resolution)



#### Device Overview:



## **Technical Specification**

Dimension : 600 x 30 x 60 Weiaht : 750 Grams Operating Temp : 0° ~ +50°(Celsius) Storage Temp : -10° ~ +60°(Celsius) Battery : 2 x AAA (3V)

#### Cleaning

- · Keep the level dry and clean. Remove any moisture or dirt with a soft, dry cloth.
- · Do not use harsh chemicals, strong detergents or cleaning solvents to clean the level.
- · Do not submerge device in water while cleaning. Wiping or cleaning on device surface is sufficient



Product of Singapore

### **Battery Compartment**



Open the rubber protector



For the first time usage, remove the plastic to connect the battery

### Calibration Instruction

- Turn on the device, Press 'CAL' button once, the screen will display flashing "CAL1"
- 2. a Place the device on a flat and clean surface, press "MODE" button once, the screen will display countdown, wait until screen countdown reach "0" and show "CAL2".
  - b Rotate the device (180°) parallel to the surface then press "MODE" button again, the screen will display countdown, wait until screen countdown reach "0" and show "CAL3".
- C Position the device vertically (-90°) on a level surface, press "MODE" button again, the screen will display countdown, wait until screen countdown reach "0" and show "CAL4".
- Rotate the device 180° parallel vertically to the surface (+90°) then press "MODE" button again, the screen will display countdown, wait until screen countdown reach "0".
- Calibration Done

Note: Ensure the device is kept still during calibration



#### **A** Caution

Digi-Pas® device is calibrated in the factory for maximum accuracy. User can re-calibrate when necessary.

Refer to www.digipas.com for video demonstration on how to calibrate the device

### **Calibration Illustration**

®Registered Design



Sten 2 Press Mode button ONCE





# Warranty

The Digi-Pas Digital level is warranted to the original purchaser to be free from defects in workmanship and material. JSB Tech will, at its option, repair or replace any detective part which may malfunction under normal and proper use within a period of 1 (one) year from the date of shipment. The foregoing warranty shall not apply to defects resulting from misuse, abuse or transfer by the Buyer, Buyer-supplied software or interfacing, unauthorized modification or operation outside of environmental specifications for the product. JSB Tech does not warrant that the operation of the instrument software, or firmware, will be uninterrupted or error free. The exclusive remedy under any and all warrants and guarantees, expressed herein, and we shall not be liable for damages from loss or delay of equipments uses. consequential, or incidental damage. No other warranty is expressed or implied. JSB Tech specifically disclaims the implied warranties of merchantability and fitness for a particular purpose.



Manufactured by JSB TECH Pte Ltd

Email: info@digipas.com

www.digipas.com

JIM-2-00602-99-001